

AMENDMENTS TO THE CLAIMS:

1. (Previously Presented) A method for investigating structural integrity, comprising:

providing a carrier member having an engagement surface, a plurality of electromechanical transducer elements being attached to said carrier member, said transducer elements being spaced from each other;

placing said engagement surface in contact with a solid structural member, so that a substantial portion of said carrier member and a plurality of said transducer elements are in effective wave-transmitting engagement with said structural member;

after the placing of said engagement surface in contact with said structural member, energizing at least a first one of said transducer elements to transmit pressure waves into said structural member;

receiving, by at least a second one of said transducer elements, pressure waves reflected from an internal structural defect in said structural member in response to the pressure waves transmitted into said structural member; and

analyzing the received pressure waves so as to detect said structural defect.

2. (Original) The method defined in claim 1, further comprising:

generating a signal encoding an image of said structural defect from the analyzed pressure waves; and

presenting said image on a display.

3. (Original) The method defined in claim 2, further comprising operating a computer to highlight a selected feature of said structural defect on said display.

4. (Previously Presented) The method defined in claim 3 wherein the highlighting of said structural defect includes varying video image intensity in a portion of a video image on said display.

5. (Original) The method defined in claim 2, further comprising operating a computer to select said image from among a multiplicity of possible images of said structural defect.

6. (Original) The method defined in claim 2, further comprising operating a filter stage to eliminate a selected artifact from said image.

7. (Original) The method defined in claim 1 wherein the analyzing of the received pressure waves includes operating a digital computer to derive a digital or electronic model of said structural defect.

8. (Original) The method defined in claim 7 wherein analyzing of the received pressure waves further includes operating said computer to perform an automated diagnosis or evaluation of said structural defect based in part on said digital or electronic model of said structural defect.

9. (Original) The method defined in claim 8 wherein the performance of said automated diagnosis or evaluation of said structural defect includes operating said computer to automatically compare said digital or electronic model with digital or electronic models of known structural defects stored in a memory of said computer.

10. (Previously Presented) The method defined in claim 1 wherein said carrier member includes a flexible web, said engagement surface being a surface of said web, the placing of said engagement surface in contact with said structural member including wrapping said web around at least a portion of said structural member.

11. (Previously Presented) The method defined in claim 10 wherein said transducer elements are mounted to said web, the placing of said engagement surface in contact with said structural member including placing at least said first one and said second one of said transducer elements in contact with said structural member.

12. (Currently Amended) The method defined in claim 1 wherein said carrier member includes at least one substantially rigid panel and a flexible web connected to said panel to form a bag along said panel, said engagement surface being a surface of said web, the placing of said ~~flexible~~ engagement surface in contact with said structural member including placing said flexible web in contact with said structural member, the placing of said ~~flexible~~ engagement surface in contact with said structural member further including feeding a fluid to said bag to press said web against said structural member.

13. (Currently Amended) The method defined in claim 12 wherein said transducer elements are mounted to said web, the placing of said ~~flexible~~ engagement surface in contact with said structural member including placing at least said first one and said second one of said transducer elements in contact with said structural member.

14. (Currently Amended) The method defined in claim 12 wherein said panel is one of a plurality of panels, the placing of said ~~flexible~~ engagement surface in contact with said structural member including placing said bag so that said engagement surface faces said structural member and so that said panels are disposed on an outer side of said bag, away from said structural member, the placing of said ~~flexible~~ engagement surface in contact with said structural member further including fastening said panels to one another about said structural member to limit expansion of said bag upon feeding of said fluid thereto.

15. (Original) The method defined in claim 12 wherein at least some of said transducer elements are disposed on said panel, said fluid being a liquid, the transmitting of said pressure waves into said structural member including transmitting said pressure waves through said liquid in said bag.

16. (Currently Amended) The method defined in claim 1 wherein the placing of said ~~flexible~~ engagement surface in contact with said structural member includes placing said engagement surface in engagement with at least two surfaces of said structural member extending at a substantial angle relative to one another.

17. (Currently Amended) The method defined in claim 1 wherein the placing of said ~~flexible~~ engagement surface in contact with said structural member includes fastening said carrier member to said structural member.

18. (Original) The method defined in claim 1 wherein the analyzing of the received pressure

waves includes determining therefrom a three-dimensional shape of said structural defect.

19. (Original) The method defined in claim 1 wherein the transmitting of said pressure waves into said structural member includes producing said pressure waves in a plurality of different frequency ranges, the receiving of pressure waves reflected from said structural defect including sensing pressure waves in said plurality of different frequency ranges.

20. (Original) The method defined in claim 1 wherein said transducer elements are mounted to said carrier member in a predetermined array, further comprising energizing said transducer elements in a predetermined sequence.

21. (Original) The method defined in claim 1 wherein the pressure waves transmitted into said structural member include ultrasonic frequency pressure waves.

22. (Previously Presented) An apparatus for investigating defects in structural members, comprising:

a carrier member having an engagement surface disposable in effective wave-transmitting engagement with a structural member;

a plurality of electromechanical transducer elements attached to said carrier member, said transducer elements being spaced from each other;

a frequency generator operatively connected to at least a given one of said transducer elements for energizing said given one of said transducer elements to transmit pressure waves into said structural member; and

a frequency processor operatively connected to at least another one of said transducer elements to process pressure waves received by said another one of said transducer elements from an internal structural defect in said structural member in response to the pressure waves transmitted from said given one of said transducer elements, said processor including means for analyzing the received pressure waves to detect said structural defect.

23. (Previously Presented) The apparatus defined in claim 22 wherein said carrier member includes a pressurizable bag for conforming said engagement surface to said structural member, further comprising an expansion restrictor surrounding said bag for limiting outward expansion thereof in a direction opposite said structural member.

24. (Original) The apparatus defined in claim 23 wherein said expansion restriction includes a plurality of rigid panels movably connected to one another and locks of fasteners operatively connected to said panels.

25. (Original) The apparatus defined in claim 22, further comprising imaging means for generating a signal encoding an image of said structural defect from the analyzed pressure waves, said imaging means being operatively connected to a display for presenting said image to a viewer or operator.

26. (Original) The apparatus defined in claim 22 wherein said processor includes means for deriving a digital or electronic model of said structural defect from the analyzed pressure waves.

27. (Original) The apparatus defined in claim 26 wherein said processor further includes means for executing an automated diagnosis or evaluation of said structural defect based in part on said digital or electronic model of said structural defect.

28. (Currently Amended) The apparatus defined in claim ~~[[22]]~~ 12 wherein said transducer elements are mounted to said bag along a flexible panel thereof.